

Grind Number:	<b>SEH2024AL</b>		
Lobe Separation:	<b>111°</b>		
Installed Centerline:	<b>107°</b>		
	<u>Intake</u>	<u>Exhaust</u>	
Lobe Lift:	<b>.335"</b>	<b>.345"</b>	
Valve Lift w/ 1.5 Ratio:	<b>.503"</b>	<b>.518"</b>	
Valve Lift w/ 1.6 Ratio:	<b>.536"</b>	<b>.552"</b>	
Standard Lifter Pre-Load	<b>.080"-.095"</b>		
Duration @ .050"	<b>220°</b>	<b>224°</b>	
Cam Timing @ .050" Tappet Lift			
	<u>Intake</u>	<u>Exhaust</u>	
Opens:	<b>3° BTC</b>	<b>47° BBC</b>	
Closes:	<b>37° ABC</b>	<b>-3° ATC</b>	
Valve Spring Requirements			
Rocker Ratio	Spring P/N	Closed Pressure	Open Pressure
1.5	<b>1110</b>	<b>120#@1.660"</b>	<b>300#@1.160"</b>
1.6	<b>1110</b>	<b>120#@1.660"</b>	<b>300#@1.160"</b>



Ph:(309)745-9558  
Fax:(309)296-9990