

## Corrected Torque and Power

Engine Speed RPM	STPPwr CHp	STP TRQ Clb-ft	A/F Ratio	VolEff %
3200	274.6	450.7	13.88	86.4
3300	280.9	447.1	13.81	83.9
3400	286.8	443.1	14.08	82.1
3500	291.6	437.6	14.09	80.6
3600	298.9	436.1	14.21	79.4
3700	306.5	435.1	13.86	79.4
3800	312.7	432.1	14.35	80.0
3900	317.1	427.1	14.63	80.2
4000	326.9	429.3	15.24	80.7
4100	338.8	434.0	15.69	80.5
4200	350.9	438.8	15.88	79.4
4300	380.8	465.2	16.55	80.8
4400	429.5	512.7	16.35	84.9
4500	450.0	525.7	15.54	88.8
4600	482.4	550.8	15.29	94.2
4700	497.2	555.5	15.11	97.0
4800	522.0	571.2	14.75	100.3
4900	536.8	575.4	14.60	103.8
5000	553.3	581.9	14.26	106.4
5100	569.0	585.9	14.05	107.2
5200	578.4	584.2	14.22	107.9
5300	590.2	584.8	14.00	110.2
5400	601.4	585.0	14.33	110.0
5500	607.3	579.9	13.63	109.8
5600	616.3	578.0	13.50	109.6
5700	618.5	569.9	14.01	108.9
5800	624.4	565.4	13.76	108.5
5900	645.7	574.8	13.98	110.8
6000	648.0	567.2	14.02	110.6
6100	657.8	566.4	14.03	110.0
6200	665.8	564.0	14.22	111.0
6300	672.3	560.5	13.94	110.2
6400	678.2	556.5	14.20	110.7
6500	685.3	553.7	13.50	110.9
6600	693.7	552.0	12.99	110.7
6700	700.6	548.9	13.71	111.5
6800	701.6	541.9	13.74	109.9
6900	692.5	527.1	13.55	108.3
7000	683.6	512.9	15.00	108.0